

1. non flicker
2. THD : 9%
3. efficiency : 91%
4. ripple current : 1%
5. PF : 0.98


Features

- Constant current output
- Isolated
- Protections: Short circuit / Over current / Over voltage / Over temperature
- Fully isolated plastic case with terminal block style of I/O
- Built-in active PFC function, comply with EN61000-3-2
- High reliability

Applications

- Indoor LED lighting
- LED office lighting
- LED commercial lighting
- LED decorative lighting


SPECIFICATION

MODEL		LDNF2-36-500-R
OUTPUT	Voltage Range @ CC	51 ~ 72V
	Constant Current	0.5A
	Ripple Current	1%
	Max. Output Power	36W
INPUT	Voltage Range	220-240VAC
	Frequency Range	47 ~ 63Hz
	Power Factor (Typ.)	Typ 0.98
	THD	THD: 9% @ Full Load 230VAC
	Efficiency(Typ.)	91% @ Full Load
	Leakage Current	<0.25mA / 240VAC
PROTECTION	Short Circuit	recovers automatically after fault condition is removed.
	Over Temperature	Shut down o/p voltage, re-power on to recover
	Working	-20 ~ +50 °C
	Working Humidity	20 ~ 95% RH non-condensing
	Storage condition	-40 ~ +80 °C, 10 ~ 95% RH
	Surge Protection	3KV
SAFETY&EMC	Withstand Voltage	I/P-O/P:3.75KVAC
	Isolation	I/P-O/P:100M Ohms / 500VDC / 25 °C / 70% RH
	EMC Emission	Compliance to EN55015, EN61000-3-2 Class C (Pin ≥ 25W), Class D (>70% load); EN61000-3-3
	EMC Immunity	Compliance to EN61000-4-2,3,4,5,6,8,11, EN55024, EN61547, light industry level, criteria A
OTHERS	Dimension	132*45*26mm (L*W*H)
	Package	0.11Kg per unit, 33pcs per inner box, 165pcs per carton
		18.2KG N.W, 20KG G.W Carton Dimension: 44.3x32.3x30.3CM 0.05CBM 3960pcs/pallet 24 carton/pallet, Pallets Size:1.0*1.0*1.36M
NOTE	All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25 °C of ambient temperature.	

Mechanical Specification
